

## DS-PHA Series Hybrid Security Control Panel

DS-PHA series hybrid security control panel, containing on-board zones, supports wired/wireless alarm inputs and outputs expanding. It works with Wi-Fi, LAN, GPRS, and 3G/4G communication methods, as well as ISAPI, ISUP, and DC09 protocol. It is applicable to the scenarios of market, store, house, factory, warehouse, office, etc.



### Available Models


- DS-PHA20-P  
SAP: 302401397
- DS-PHA64-M  
SAP: 302401466
- DS-PHA20-W2P: supports Wi-Fi and short video verification  
SAP: 302401439
- DS-PHA64-W4M: supports Wi-Fi and short video verification  
SAP: 302401467
- DS-PHA64-W4P: supports Wi-Fi and short video verification  
SAP: 302401394
- DS-PHA64-B (PCB only)  
SAP: 302401497
- DS-PHA64-W4B (PCB only): supports Wi-Fi and short video verification  
SAP: 302401501
- DS-PHA64-P2  
SAP: 302401709
- DS-PHA64-W4P2: supports Wi-Fi and short video verification  
SAP: 302401714




## Features

- Dual path communication of alarm events and other signals over LAN, PSTN, Wi-Fi (-W model), GPRS and 3G/4G utilizing a main and backup channel with configurable priority
- 4/8 on-board wired zones, and expandable with up to 20/64 wired zones
- Up to 16/56 wireless inputs, 18/60 wireless outputs, 8 keyfobs, 1 wired siren and 2 wireless sirens
- Camera accessing (only supported by DS-PHAXX-W2/4)
- Pre-alarm (5 s) and post-alarm (2 s) recording for video verification to the alarm receiving email or mobile client
- Uploads alarm events to alarm receiving center or platform.
- Supports arming/disarming via keypad, mobile client, iVMS-4200, SMS, and tag
- Configuration via web client, Hik-Connect, or iVMS-4200
- Pushes alarm notification via messages
- Alarm video clips via emails and APP
- AES-128-bit data encryption
- LED indicator for indicating system status
- Expandable PSTN, 3G/4G, and GPRS interface
- Supports RS-485 input and output expander
- Supports lithium battery (-P model) or storage battery (-M model)
- 1 manufacturer, 1 installer, 1 administrator, and 13 users (DS-PHA20)/45 users (DS-PHA64)

# Typical Application





Model	DS-PHA20-P DS-PHA64-P2 DS-PHA64-B DS-PHA64-M	DS-PHA20-W2P DS-PHA64-W4M DS-PHA64-W4P DS-PHA64-W4P2 DS-PHA64-W4B
Device connection	Wireless Detector	Up to 16/56
	Wireless Output expander	Up to 8
	Siren	1 wired siren (on-board connection) 2 wireless sirens
	Keyfob	8
	Partition	4 (DS-PHA20) 8 (DS-PHA64)
Alarm input	Zone	4 on-board zones , and 16 wired/wireless zones expandable (DS-PHA20) 8 on-board zones, and 56 wired/wireless zones expandable (DS-PHA64)
		Alarm output
Function	Scheduled arming/disarming	Supported
	SMS notification (with 3G/4G/GPRS module)	Supports up to 8 mobile phone numbers
	Network camera accessing	N/A 2 (DS-PHA20) 4 (DS-PHA64)
Application & Protocol	Application	iVMS-4200 (client software) Hik-Connect (mobile client)
	Protocol	ISAPI: Supports client software and web client Cloud P2P: Supports cloud P2P privacy protocol DC09: ARC accessible (CID/SIA)
Network	Wired network	10M/100M Ethernet
	Cellular Network (with 3G/4G/GPRS module)	Supports report push-notification to ARC & Cloud
	Standard	N/A 802.11b/g/n
Wi-Fi	Encryption	N/A 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
	Configuration	N/A AP Mode
	Distance	N/A Indoor: ≤ 50 m Outdoor: ≤ 100 m
Interface & Component	TAMPER Switch	1, front cover tamper-proof
	Network Interface	1, RJ45 10M/100M Ethernet Interface
	Telephone Interface	1, PSTN expander interface

User	RS-485 Terminal	1, extended up to 20 inputs/outputs (with RS-485 module), and 9 wired keypads extendable (DS-PHA20) 1, extended up to 64 inputs/outputs (with RS-485 module), and 9 wired keypads extendable (DS-PHA64)	
	Siren Power Interface	1, 12V	
	Battery Interface	Lithium battery (-P model) Storage battery (-M model/-P2 model)	
	User	Installer: 1 Administrator: 1 Manufacturer:1 Operator: 13 (DS-PHA20), 45 (DS-PHA64)	
	Power	100 to 240 VAC, 50/60 HZ	
	Current	3 A Max	
	Operation Temperature	-10 °C to 55 °C (-4 °F to +122 °F)	
Others	Operation Humidity	10% to 90% (No condensing)	
	Dimension (W × H × D)	Plastic Case: 220 mm (8.6") × 152 mm (6.0") × 31.5 mm(1.2") -P2 Plastic Case: 310 mm (12.2") × 225 mm (8.6") × 95 mm (3.7") Metal Case : 351.4 mm (13.8") × 261.4 mm (10.3") × 93.3 mm (3.7")	
	Weight	DS-PHA20-M: 3.6 Kg DS-PHA64-M: 3.6 Kg DS-PHA20-P: 0.8 Kg DS-PHA64-P2: 1.15 kg	DS-PHA64-W4M: 3.7 Kg DS-PHA20-W2P: 0.8 Kg DS-PHA64-W4P: 0.8 Kg DS-PHA64-W4P2:1.17 kg

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com