



MC100CM

Convertidor Multimedia Multi-modo de 10/100Mbps

MÓDULO Y CONVERTIDOR DE MEDIOS

Estándares y protocolos	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Función básica	Half/Full-Duplex transfer mode for FX port Full Duplex Flow Control (IEEE 802.3x) Half Duplex Flow Control (Backpressure) Extends fiber distance up to 2km

MÓDULO Y CONVERTIDOR DE MEDIOS

	Link Fault Passthrough and Far End Fault minimize the loss caused by link failure timely
Puertos	1 100M SC/UPC port 1 100M RJ45 port (Auto MDI/MDIX)
Longitud de onda	1310nm
Medios de red 10BASE-T	UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Medios de red 100BASE-T	UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Medios de red 100BASE-FX	Multi-mode Fiber
Dimensiones (Al x An x Pr)	3.7*2.9*1.1 in. (94.5*73.0*27.0 mm)
Fuente de alimentación	External power supply
Consumo máximo de energía	2.5W
LED	PWR, FDX/Col, Link/Act, SPD
Seguridad y emisión	FCC, CE, RoHS
Package Content	• Media Converter MC100CM • Power Adapter • Installation Guide
Ambiente	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

Síguenos

About

Press

Partners

Learning Center

Argentina / Español

TP-Link

Omada

Omada

Wi-Fi 6E

Copyright © 2025 TP-Link SRL Reservados todos los derechos.